

I34

HIGHLY MOBILE COMPACT CRUSHER

The McCloskey™ I34 compact impact crushers is the perfect solution for projects with small footprints but big requirements. These compact, mobile crushers are suited particularly to construction and demolition recycling, asphalt recycling, and aggregates

This versatile, mobile crusher is able to nimbly move around in small spaces, and continue moving while crushing. The I34R's small footprint is uniquely suited to the demolition and asphalt recycling, aggregates and smaller scale construction projects. Less than 2.5m wide, the crushers can be transported easily from site to site.

The new line boasts flexibility as well Not only can the I34 continue crushing while moving, it can convert to a recirculating impactor in just a few hours.



SCREENBOX

High Energy Screenbox has user-friendly wedge system for faster screen change.



LARGE FEEDER

Hopper mounted over vibrating feeder. Feeder rate can be regulated via mechanical Flow Control

DIRECT DRIVE CRUSHER

34 x 25.6" feed opening to new direct drive crusher more power, along with lower fuel costs



MAGNET

Reversible magnet enables material separation from the source material.

Engine	350 hp (261 kW) Diesel
Transport Height	11' 1.8" (3.40m)
Transport Length	47' 5.9" (14.48m)
Transport Width	8' 2.5" (2.50m)
Weight - w/ magnet & side conveyor	96,783 lb (43,900kg)
Crushing Chamber	45" (wide) x 27" (pitman opening)
Stockpile Height - Main Conveyor	12' 8.7" (3.88m)
Stockpile Height - Side Conveyor	8' 2.3" (2.50m)
Optional Prescreen Feeder	41.9"x75.5" (1.06mx1.92m)

I34R

RECIRCULATING COMPACT CRUSHER

The McCloskey™ I34R recirculating Impact Crusher combines the productivity of our I34 with the versatility of a full screening and recirculating system, allowing operators to produce a crushed and screened final product with one machine.

This versatile, mobile crusher is able to nimbly move around in small spaces, and continue moving while crushing. The I34R's small footprint is uniquely suited to the demolition and asphalt recycling, aggregates and smaller scale construction projects. Less than 2.5m wide, the crushers can be transported easily from site to site.

The new compact crushers boast flexibility as well, with standard machines converting to recircs in just a few hours.



RADIAL RETURN CONVEYOR
Allows operators to recirculate oversize material from the screenbox back to the feed hopper or radial out up to 90° to feed another machine or stockpile up to 9' 9".

SCREENBOX

High Energy Screenbox has user-friendly wedge system for faster screen change.



LARGE FEEDER

Hopper mounted over vibrating feeder. Feeder rate can be regulated via mechanical Flow Control

DIRECT DRIVE CRUSHER

34 x 25.6" feed opening to new direct drive crusher more power, along with lower fuel costs



MAGNET

Reversible magnet enables material separation from the source material.

Engine	252 hp (188 kW) Diesel
Transport Height	10' (3.056m)
Transport Length	42' 9" (13.024m)
Transport Width	8' 4" (2.55m)
Weight (incl. magnet & dirt conveyor)	60.627 lb (27,500)
Stockpile Height - Fines Conveyor	8' 4" (2.54m)
Stockpile Height - Side Conveyor	8' 6" (2.58m)
Crushing Chamber	34" (wide) x 25.6" ()
Screenbox Dimensions	5' x 10'