

McCloskey
INTERNATIONAL

**COMPACT
CRUSHERS**

mccloskeyinternational.com





I34

The I34 and I34R are compact impact crushers from McCloskey International, and are the perfect solution for projects with small footprints but big requirements. These compact, mobile crushers are suited particularly to construction and demolition recycling, asphalt recycling, and aggregates.

COMPACT

The new Impactors (I34 and I34R) deliver high performance and expanded versatility in a highly mobile lineup to customers around the world. Able to nimbly move around in tight spaces, the lines' small footprint is uniquely suited to the recycling, demolition and smaller scale construction projects. Less than 2.5m wide, the crushers can be transported easily from site to site.



I34R

FLEXIBLE

The I34 compact crusher boasts flexibility as well. Not only can the I34 continue crushing while moving, it can convert to a recirculating impactor in just a few hours.

POWERFUL

McCloskey compact crushers are ready to take on some of the most diverse projects out there, with an average of 200+ TPH. Whether you're crushing aggregates, C&D Waste, or reinforced concrete the I34 and I34R are up to the challenge.



Aggregate



Recycled Concrete



Recycled Asphalt



Demolition Waste



SPECIFICATIONS

Output	Up to 200TPH
Feed Size	Feed size 600 x 500 x 500mm lump, (24" x 20" x 20")
Feed Opening	Feed opening W x H 860 x 650mm, (34 x 25.6")
Crusher	Crusher speed 678-756 rpm (32-35.5 m/sec rotor tip speed) Number of aprons 1, 3 strike zones Number of blowbars 4 Direct Drive Impactor weight 7, 150kg (15,763 lbs) Closed side setting adjustment - Hydraulic rams, shim system, spring tension Apron adjustment to suite either Primary or Secondary crushing
Hopper	
Grizzly Feeder	Feeder width 2102mm (82.8") Feeder length 4230mm (166.5") Hydraulic Drive Grizzly section opening Tapered 30-50mm, 35-65mm, 45-65mm Grizzly section length 1080mm (42.5")
Main Conveyor	Stockpile height 3006mm (9' - 10") Belt width (36")
Side Conveyor	Stockpile height 2583mm (8' - 6") Belt width 500mm (20")
Power Unit	Engine Volvo D8 Tier 4 Final or Tier 3 Engine power 188 Kw (252 HP)
Control System	TEDD Control System, with 4 emergency stops
Weight	27,500 kgs (60,627lbs) including magnet and dirt conveyor

OPTIONS

- ▶ Main conveyor variable speed control
- ▶ Overband magnet
- ▶ Water Pump and dust suppression system
- ▶ Various blow bar material options
- ▶ Work lights
- ▶ Grizzly punch plate/Grizzly blanking plate
- ▶ Refueling pump
- ▶ 4 feed height blowbars
- ▶ Blowbar change hoist

McCloskey
INTERNATIONAL

Headquarters

1 McCloskey Road
Keene, Ontario Canada,
K9J 0G6
1-877-Trommel
T (705) 295-4925
F (705) 295-4777
sales@mccloskeyinternational.com

European Office

47 Moor Road,
Coalisland, Co Tyrone
N.Ireland BT71 4QB
T +44 (0)2887-740-926
F +44 (0) 2887-747-242
salesuk@mccloskeyinternational.com

www.mccloskeyinternational.com

McCloskey International reserves the right to make changes to the information and design of the machines on this brochure without reservation and notification to the users. McCloskey International assumes no liability resulting from errors or omissions in this document.

Copyright 2018 McCloskey International. All rights reserved.